

LDJ-10/210-L

型电流互感器 CURRENT TRANSFORMER



上海互凌

Shanghai Huling Electric Co., Ltd.

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

● 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards

● 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV

● 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz

● 额定二次电流: 5A或1A
Rated secondary current 5A or 1A


● 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				一秒热稳定电流 1s thermal current(kA)	动稳定电流 Rated dynamic current(kA)		
		0.2(S)	0.2	0.5	5P10				
5	0.2(S)/0.2(S) 0.2(S)/0.5(S) 0.5(S)/0.5(S) 0.2(S)/5P10 0.5(S)/5P10	10	10	15	15	0.6	1.5		
10						1.1	2.75		
15						1.7	4.25		
20、25						2.7	6.75		
30						4	10		
40						5	12.5		
50						9	22.5		
75						13.5	33		
100						18	45		
150						27	63		
200、250			10			15	20	63	100
300、400									
500、800									
1000、1250									
		20	20	25	80	130			

外形及安装尺寸 Overall dimension drawing

LDJ-10/210-L 5-250A



LDJ-10/210-L 300-1250A

