

◆ 型号含义 Type description

L Q Z B J - 10 Q

全工况 Intensive insulation type
 额定电压 (kV) Rated voltage(kV)
 加强型 Strengthen
 带有保护级 With protective class
 浇注绝缘 Cast-resin insulated
 线圈式 Coil type
 电流互感器 Current transformer



◆ 技术参数 Technical data

产品型号 Type	额定电流比 Rated transformation ratio(A)	级次组合 Accuracy Classes combination	准确级及额定输出 (VA) Accuracy class and rated output COS ϕ = 0.8				一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current(kA)
			0.2S	0.2	0.5	10P10		
LQJ8-10Q LQZBJ-10Q	5/5	0.2S/10P10 0.2/10P10 0.5/10P10	10	10	10	15	0.5	1.1
	10/5						0.9	2.3
	15/5						1.4	3.4
	20/5						1.8	4.5
	30/5						2.7	6.8
	40/5						3.6	9
	50/5						4.5	11.3
	75/5						6.5	16.9
	100/5						9	22.5
	150/5						11.3	24
	200/5						15	32
	300/5						22.5	48
	400/5						30	64
	500/5						32	80
	600/5							

注：用户如有特殊要求可与我公司协商确定，动热稳定可按用户要求。

Note: Any special requirements can be negotiated with us, thermal and heat both stable, we can customized your requirement.

◆ 外形及安装尺寸 Overall dimension drawing

